

T-13/4 (5 mm), Wide Viewing Angle, High Intensity LED Lamps

Technical Data


HLMA-VH00
HLMA-VL00
HLMP-V100
HLMP-V500

Features

- Outstanding LED Material Efficiency
- Extremely Wide Horizontal Viewing Angle
- High Light Output over a Wide Range of Currents
- Untinted, Non-diffused Lens
- Choice of Four Colors: 644 nm Red, 590 nm Amber, 570 nm Green, and 615 nm Orange

Description


These high intensity LED lamps provide the user with an extremely wide 60° (horizontal) by 30° (vertical) oval shaped radiation pattern. Available in TS AlGaAs red, AlInGaP amber, AlInGaP orange, and GaP green colors, these untinted non-diffused T-1³/₄ (5 mm) LEDs are an excellent choice for outdoor applications requiring an extremely wide field of vision and high brightness.



Applications

- Outdoor Message Boards
- Safety Lighting Equipment
- Changeable Message Signs
- Alternative to Incandescent Lamps

Outline Drawing



Device Selection Guide

Amber $\lambda_d = 590 \text{ nm}$	Red-Orange $\lambda_d = 615 \text{ nm}$	Red $\lambda_d = 644 \text{ nm}$	Green $\lambda_d = 570 \text{ nm}$
HLMA-VL00	HLMA-VH00	HLMP-V100	HLMP-V500

NOTES:

1. LEAD ORIENTATION:

DEVICE TYPE	CENTER LEAD	OUTER LEADS
HLMP-V100	COMMON ANODE	CATHODE
HLMP-V500	COMMON CATHODE	ANODE
HLMA-VL00	COMMON CATHODE	ANODE
HLMA-VH00	COMMON CATHODE	ANODE

2. ALL DIMENSIONS ARE IN MM (INCHES).

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Parameter	HLMA-VL00	HLMA-VH00	HLMP-V100	HLMP-V500	Units
DC Forward Current ^[1,3]	60 ^[4,5]	60 ^[4,5]	60	50	mA
Peak Forward Current ^[2,3]	400	400	600	180	mA
Average Input Power ^[2]	120	120	120	110	mW
Reverse Voltage ($I_R = 200\ \mu\text{A}$)	5	5	5	5	V
Operating Temperature Range	-40 to +100	-40 to +100	-55 to +85	-20 to +100	$^\circ\text{C}$
Storage Temperature Range	-55 to +100	-55 to +100	-55 to +100	-55 to +100	$^\circ\text{C}$
Junction Temperature	110				$^\circ\text{C}$
Soldering Temperature [1.59 mm (0.06 in.) below seating plane]	260 $^\circ\text{C}$ for 5 seconds				

Notes:

- Derate linearly as shown in Figure 5.
- Any pulsed operation cannot exceed the Absolute Max Peak Forward Current or the Max Allowable Average Power as specified in Figure 6.
- Specified with both die powered simultaneously.
- Drive Currents between 10 mA and 30 mA are recommended for best long term performance.
- Operation at currents below 10 mA is not recommended, please contact your Hewlett-Packard sales representative.

Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Luminous Intensity I_V (mcd) @ 40 mA ^[1]		Peak Wavelength λ_{peak} (nm) Typ.	Color, Dominant Wavelength λ_d ^[2] (nm) Typ.	Viewing Angle $2\theta_{1/2}$ Degrees ^[3] Typ.	Luminous Efficacy η_V (lm/w)
	Min.	Typ.				
HLMA-VL00	212	460	592	590	60° horizontal 30° vertical	480
HLMA-VH00	200	460	621	615		263
HLMP-V100	500	1000	654	644	60° horizontal 30° vertical	85
HLMP-V500	112	270	568	570	60° horizontal 30° vertical	595

Notes:

- The luminous intensity, I_V , is measured at the mechanical axis of the lamp package. The actual peak of the spatial radiation pattern may not be aligned with this axis.
- The dominant wavelength, λ_d , is derived from the CIE Chromaticity Diagram and represents the color of the device.
- $2\theta_{1/2}$ is the off-axis angle where the luminous intensity is 1/2 the on-axis intensity.

Electrical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Forward Voltage V_F (Volts) @ $I_F = 40\ \text{mA}$		Reverse Breakdown V_R (Volts) @ $I_R = 200\ \mu\text{A}$	Capacitance C (pF) $V_F = 0$, $f = 1\ \text{MHz}$	Thermal Resistance $R_{\theta J-PIN}$ ($^\circ\text{C}/\text{W}$)	Speed of Response τ_s (ns) Time Constant e^{-t/τ_s}
	Typ.	Max.				
HLMA-VL00	1.90	2.4	5	120	100	13
HLMA-VH00	1.90	2.4	5	120	100	13
HLMP-V100	1.85	2.4	5	50	115	26
HLMP-V500	2.20	3.0	5	20	100	171




Figure 2a. Forward Current vs. Forward Voltage, HLMA-VL00/VH00.




Figure 2b. Forward Current vs. Forward Voltage, HLMP-V100.




Figure 2c. Forward Current vs. Forward Voltage, HLMP-V500.




Figure 3. Relative Luminous Intensity vs. Forward Current.




Figure 4a. Relative Efficiency vs. Peak Forward Current, HLMA-VL00/VH00.




Figure 4b. Relative Efficiency vs. Peak Forward Current, HLMP-V100.




Figure 4c. Relative Efficiency vs. Peak Forward Current, HLMP-V500.




Figure 5a. Maximum Forward DC Current vs. Ambient Temperature, HLMA-VL00/VH00.




Figure 5b. Maximum Forward DC Current vs. Ambient Temperature, HLMP-V100.




Figure 5c. Maximum Forward DC Current vs. Ambient Temperature, HLMP-V500.




Figure 6a. Maximum Allowable Average Power vs. Ambient Temperature, HLMA-VL00/VH00.




Figure 6b. Maximum Allowable Average Power vs. Ambient Temperature, HLMP-V100.




Figure 6c. Maximum Allowable Average Power vs. Ambient Temperature, HLMP-V500.




Figure 7a. Relative Intensity vs. Angle, HLMA-VL00/VH00 Horizontal Axis.




Figure 7b. Relative Intensity vs. Angle, HLMA-VL00/VH00 Vertical Axis.




Figure 8a. Relative Intensity vs. Angle, HLMP-V100 Horizontal Axis.




Figure 8b. Relative Intensity vs. Angle, HLMP-V100 Vertical Axis.




Figure 9a. Relative Intensity vs. Angle, HLMP-V500 Horizontal Axis.




Figure 9b. Relative Intensity vs. Angle, HLMP-V500 Vertical Axis.